

Artistry In Motion, Inc.

19411 Londelius Street, Northridge, CA 91324 Tel: (818) 994-7388 Fax: (818) 994-7688

Material Safety Data Sheet

Date of preparation 5/27/98

PVC Film

Section I

Product Name: Metallized Colored PVC Film
Common Name: Colored Metallized Vinyl Film
Chemical Name: Polyvinyl Chloride Calendered Rigid Film/
Acrylic Resin

Section II

INGREDIENTS

COMPONENT	CAS #	%	PEL/TLV
PVC	Not Listed	93	N/A
Acrylic Resin	Proprietary	4	N/A
*Pigment	Proprietary		Not Established
Aluminum			N/A

*No Heavy Metals as defined in CONTG LEGISLATION

Section III

Boiling Point: NA Evaporation Rate: ND
pH: NA
Solubility in Water: None over 24 hours
Appearance: Brightly colored metallic plastic film

Section IV

FIRE AND EXPLOSION HAZARD

Flammability Classification: Will not ignite
LEL: Not applicable
Unusual Fire and Explosion Hazards None
Special Firefighting Procedures: Use self contained breathing apparatus to protect against hazardous fumes which are produced by combustion or h temperature decomposition.

Section V

HEALTH HAZARD DATA

Below decomposition temperature the product has no significant toxic hazard.

First aid measures if exposed to fumes:

Disposal method:

Skin: Flush skin thoroughly with cool water for at least 5 minutes.

Eyes: Immediately flush eyes with a directed stream of water for at least 15 minutes while forcibly holding eyelids apart. Get medical attention.

Inhalation: Remove to fresh air. If breathing is difficult, administer oxygen. If respiration stops, give mouth to mouth resuscitation. Get medical attention.

Section VI

PHYSICAL HAZARD

Stability: Stable

Condition to avoid: Extreme heat

Incompatible materials: Organic Solvent Inorganic Acids

Hazardous decomposition products: CO₂, CO
Nitrous Oxides
HCL

Section VIII

SPECIAL PROTECTION INFORMATION

TLV or suggested control value:

No TLV is assigned to this mixture. Minimize exposure to dust that may be generated during processing operations such as slitting or punching in accordance with good hygiene practices.

Ventilation:

Remove decomposition fumes with local exhaust if overheating occurs during processing at 300 degrees C.

Respiratory protection (specify type):

If needed, use MSHA-NIOSH approved respirator for dust, mists and fumes with concentrations greater than 0.05 mg/m³.

Protective clothing:

Use work gloves to avoid cuts from sharp edges. Protect from thermal effects with heated material.

Eye protection:

Safety glasses with side shields.

Other protective equipment:

Eyewash station in work area.

The information and recommendations contained herein are based on standard product and a proprietary and furnished solely for the use of our customers. Since it is impossible for us to determine the precise conditions under which our product will be used, neither Artistry In Motion nor its affiliates can accept responsibility for loss, injury or other damages resulting from the use of the product or this or any other information provided by us. Users are advised make their own tests to determine the safety, suitability and relevance of Federal and Local Laws to the product as it is to be used by them. Therefore, unless otherwise agreed in a signature writing, **NO GUARANTEES OF ANY KIND, INCLUDING THOSE FITNESS OR MERCHANTABILITY ARE MADE BY ARTISTRY IN MOTION, INC. OR ITS AFFILIATES** with regard to any c