



## Loading & Firing Instructions for The Silent Storm SS™ Confetti Spreader

### **How to Setup the Silent Storm SS™ System:**

- 1) Unlatch all four latches and remove the road case lid.
- 2) Pull out the aluminum rod and pull out the electric cord attached to the motor.
- 3) Lift motor to the up position and insert the aluminum rod so that the rod extends from one side of the case to the other.
- 4) Select the location you desire to place the Silent Storm™. The Silent Storm™ is designed to be hung from below a truss, or to span across the top of a truss.

**Note:** Aim the Silent Storm™ carefully to avoid pointing it at anyone or anything.

- 3) Load the confetti into the loading door, which is located on the top of the Silent Storm™.

**Note:** Make sure the confetti is fluffed thoroughly to achieve the best performance.

- 4) Using aircraft cables attach the cannon to the truss or hanging point or ratchet strap the unit to the top of a truss. Make sure the Silent Storm™ is secure and the cables or ratchet straps are backed up with a redundant safety cable.
- 5) Connect the Silent Storm™ power cord using extension cords as necessary to the control box or to an alternative control device. A dim circuit on a lighting board is a typical alternative. The Silent Storm™ requires 110V 60 cycle AC and draws 4 amps. Typical U.S.A. electrical circuits supply 20 amps. If you are using more than one Silent Storm™ we recommend that no more than 3 units to be run on a single 20-amp circuit.

### **How to use the Silent Storm SS™ System:**

- 1) Turn the switch power to the “ON” position. Depending on the effect you want to create, you can vary the fan speed to control the flow of confetti. If desired, you can start the fan at 100%, and once the flow has begun, dial the power to a reduced, sustained level.
- 2) When the desired effect is complete turn the switch power back to the “OFF” setting.

### **How to Disconnect / Pack-up the Silent Storm SS™ System:**

- 1) After disconnecting the power source from the unit, safely lower the unit back down to the ground and detach all rigging cables from unit and lay the cables and extra power cords on top of unit.
- 2) Make sure you remove any extra confetti from inside the unit and then remove the aluminum rod and lower the motor back to the down position for transport. Place the aluminum rod inside the case.
- 3) Now place the lid back on top of the unit and latch all 4 latches for shipping.

**SPECIAL EFFECTS CAN BE DANGEROUS.** Please carefully read the above directions before use. The Silent Storm™ should be used by professionals who have been properly instructed in their use. Never aim the Silent Storm™ confetti at anyone or anything. Use at your own risk.

**\*\*IF FURTHER INSTRUCTION IS NEEDED, PLEASE CALL 818-994-7388\*\***

**e-mail: [confetti@artistryinmotion.com](mailto:confetti@artistryinmotion.com)**

**Artistry In Motion, Inc**  
**15101 Keswick Street Van Nuys, CA 91405**  
**Tel: 818.994.7388 Fax: 818.994.7688 Website: [www.artistryinmotion.com](http://www.artistryinmotion.com)**